MUSCLE TOOLS Q3 2024 EDITION

HIGH TECH TO HARD TECH

BOSCH ROBINAIR OTC The most advanced diagnostics, tools & equipment

Exclusive Promotion for DCU 100 **Tablet Owners**

Save big when you upgrade your DCU 100 tablet to the latest HDS 1000 tablet (3824A-TBL)



Save up to \$1000 See page 3





EXCLUSIVE PROMOTION

FOR OTC ENCORE SCAN TOOL OWNERS



Learn More

You could be eligible for a FREE ADS 525X scan tool or a \$500 rebate when you upgrade

Scan the code and enter your Encore serial number to get your exclusive offer





EVDC100 **Electronic Variable Compressor Tester**


More on page 7



#BoschSolves

Solving a vehicle with a leaky purge solenoid

Case Study: A customer came into the shop with a VW that's getting low MPGs with a check engine light. We identify the problem and find the fix using the ADS 625X scan tool, OTC 8260M Master Hook and Pick Set, Bosch SMT 500 Leak Tester, and Bosch Canister Purge Valve.



Featured and compatible products



Bosch ADS 625X
Diagnostic Scan Tool



Bosch SMT 500 Leak Tester



Learn More
Bosch Canister
Purge Valve





8260M 9260M Mag

OTC 8260M Master Hook and Pick Set

See how #BoschSolves real-world problems technicians see in their shop every day



MUSCLETOOLS

Bosch Diagnostics



3824A

ESI[truck] Heavy Duty Diagnostic Solution

Truck, engine, and system coverage

- HDS 1000 10" touchscreen Windows® 10 tablet
- Ruggedized drop-tested tablet designed for the garage environment
- Enhanced bidirectional controls
- Injector coding, forced DPF regen, VGT relearning, special tests, component actuations & more
- Proprietary ESI[truck] software saves valuable labor time with intuitive software – scan procedures the same for a Sprinter van to a Terex Titan dump truck
- All-in-one subscription unlocks access to full color-wiring diagrams, live data stream, and repair information for all makes and models
- All diagnostic functions continue after subscription expiration*

3824A-TBL

Heavy Duty Tablet Upgrade

- Everything you need to upgrade an existing 3824 ESI[truck] Tablet to the new and improved 3824A model
- Windows 10 Touchscreen tablet

3824-08R

Troubleshooting & Repair Subscription

- Faster, more efficient heavy duty vehicle repairs
- 13,000+ procedures guide user through each step to troubleshoot vehicle issues
- Procedures by DTCs or by vehicle symptoms
- Technical Service Bulletins (TSBs) included

*Applies to Truck (3824A and 3824-08) and OHW (3824CBL-UPG and 3824-080HW) Coverage

The Bosch ESI[truck] platform is unlike any other in the industry, taking heavy duty diagnostics to the next level.

3824CBL-UPG

ESI[truck] Off-Highway Upgrade Cable Kit with Introductory Software License

Add off-highway vehicle and machinery coverage for multiple manufacturers to your 3824A ESI[truck] scan tool.

Kit contents:

- 10 cables for machinery, construction equipment, agricultural vehicles and more
- ESI[truck] off-highway software package with full diagnostic capabilities. Introductory off-highway software expires when your ESI[truck] heavy duty truck software expires
- Software renewals can be done simultaneously, ensuring continuous HD truck and off-highway vehicle coverage

3824BSC

ESI[truck] Software and Adapter Kit

- Includes the ESI[truck] platform features, adapters, software, and coverage for use on your own Windows 10 device
- ESI[truck] diagnostic software with the functions and aftermarket coverage techs need, RP1210 Data link adapter, 6 and 9 pin cables, and HD/OBD II cables



ESI[truck] 1-Year Renewal License

• 1-Year (12-month) renewal license for existing ESI[truck] user

3824-080HW

ESI[truck] Off-Highway 1-Year Software License

- 12-months of off-highway diagnostic coverage, including all coverage updates
- Used to renew initial software included with Off-highway upgrade cable kit with introductory software license









For more information on software updates and off-highway coverage upgrades, visit boschdiagnostics.com

Off-highway cable upgrade kit and off-highway software only compatible with 3824A and 3824BSC ESI[truck] diagnostic tools. Customer must first purchase Off-highway upgrade cable kit with introductory software (3824CBL-UPG) prior to purchasing or activating Off-highway 1-year software license (3824-080HW)





Exclusive Promotion for DCU 100 Tablet Owners Save hig when you upgrade your DCU 100 table

Save big when you upgrade your DCU 100 tablet to the latest HDS 1000 tablet (3824A-TBL)

Scan code for offer details. Terms and conditions apply.



Buy 3824A-TBL tablet upgrade and receive

\$300 rebate




Buy 3824A-TBL tablet upgrade and 3824-08 annual software subscription and receive

\$750 rebate



Buy 3824A-TBL tablet upgrade, 3824-08 annual software subscription and 3824-08R troubleshooting software subscription and receive

\$1000 rebate



ADSX Diagnostic Scan Tools

Extreme speed. Extreme flexibility. Extreme access.

- Rapid DTC scan powers all-system DTC scans
- Complete pre- and post-reporting with wireless printing
- NEW! 100% OEM-approved access to unlock secure gateway (SGW) access to Hyundai / Kia / Genesis vehicles
- SGW access to FCA (formerly Stellantis) vehicles with AutoAuth subscription
- Access to Repair Source 100% OEM-licensed repair information library with the most expansive, reliable, and up-to-date vehicle coverage and information, right from the source
- OEM full-color wiring diagrams & enhanced bi-directional testing
- Access to Auto ID, Symptom-Assist™ Tech Tips, Code-Assist™ Top Reported Fixes
- Quick links to Indentifix, Mitchell, AllData and more
- On-tool and online training videos
- All new Android 10.0S+ software with access to Google Play Store



3920 VET 100 Circuit Analysis Tool

Quickly identify electrical issues in failed circuits

- Perfect tool for Data stream analysis using your scan tool
- Identify failed circuit component, wiring or PCM
- Simulates the sensor you are diagnosing by inputting a determined voltage at the sensor location
- Allows input voltage from .5VDC -7VDC in .5VDC increments
- Use your scan tool to verify if correct voltage is being applied to circuit
- Bypass sensor to send desired voltage back to PCM
- Works with 12V and 24V systems with vehicle voltage displayed. Also includes a "flashing" low battery voltage indicator



<u>3990</u>

OTC 1000V CAT III Hybrid Multimeter with Insulation Resistance Test

OTC 1000V CAT III Hybrid Multimeter with Insulation Resistance Test. A full function Multimeter with an insulation test feature is used to test for voltage leaks through insulation found on Hybrid and Electric Vehicles.

Features:

- Hybrid Insulation Resistance Test
- True RMS
- Auto Ranging
- Diode Test
- Continuity Buzzer
- Data Hold
- Data Logging
- Display Backlight
- Min/Max Mode
- Sleep Mode
- Low Battery Display



BAT6120-US

BAT 6120-US

Battery Charger & Power Supply

High-Power 12 V Battery Charger and 120 Amp Power Supply.

- Supports and maintains 120 A DC Continuous Output (@AC120 V~240 V, 25℃)
- Important for late model vehicles which have higher current requirements to maintain stable power supply during programming
- Supports Flooded/AGM/EFB/GEL/Lithium (LFP) batteries
- 12 V Lead Acid Battery Charge. Charging Diagnosis / 12 V Lithium Battery Charge, BMS Wake Up
- Maximum power output: up to 1750 W
- Flexible operation modes to fulfill customer needs
- Fits neatly on a desk, bench, or showroom floor.
 Also wall-mountable



BAT 35

Vehicle Computer Memory Saver

BAT 35 maintains the memory of the on-board vehicle computer to prevent losing memory settings when you disconnect a battery.

- Retain computer memory and on board memory sets such as: keyless entry codes, seat memory, digital radio settings, clocks, car alarms etc.
- Includes 12V, 7amp hour lead acid, sealed battery for long life expectancy
- Six LED indicator lights, three for charging functions and three for power storage conditions for ease of use
- Built-in OBD II cable for vehicle power supply while vehicle battery is disconnected




BAT 155

Heavy Duty Battery and Electrical System Analyzer

- 100 6,000 Cold Cranking Amp (CCA) Test Capacity
- Enables Testing Battery Packs (Multiple Batteries connected together) in the
- Infrared Temp Sensor for measuring battery temp (increases accuracy of CCA measurement)
- Optional Amp Probe and Voltmeter
- Tests 6V, 12V batteries and 12V, 24V charging systems

ADAS Recalibration System

DAS 3000



Calibration Mats

Brand specific equipment for the proper calibration of the Rear and Surround View cameras according to the OEM specifications implemented by Bosch routines and workflows.

Near Range Camera Systems for Volkswagen group



Calibration set for 360° Cameras Generation 2:

CTA 500-1

Near Range Camera **Systems for** Mercedes-Benz



Calibration set for Rear Camera: CTA 501-1



Calibration set for Rear Camera: CTA 511-1

Leak Testers

Safe and cost-effective leak detection solutions for passenger and heavy duty vehicles



SMT 500

SMT 500

Portable Leak Detector

- On Board Air compressor eliminates need for shop air or inert gas tank during use
- Variable flow control detect leaks as small as 0.01" in sealed systems
- Pressure decay testing
- Compact, lightweight design (ultra-portable at 11 lbs)



SMT 300

SMT 300

LeakTamer II **EVAP & Diagnostic Smoke Machine**

Multi-purpose tester designed not only for EVAP testing but for leak detection in any low pressure closed system including oil leaks, exhaust leaks, wind leaks, water leaks, EGR leaks and many more

- Fully featured machine with graduated smoke flow control valve, air flow meter, and pressure/ vacuum decay gauge
- Full complement of accessories and storage case included



1699500000

HPT 500

High Pressure Leak Tester

- Produces leak detection "smoke" at higher pressure than standard machines (up to 20psi) for higher pressure systems
- Higher flow rate fills the system with smoke up to 5 times faster
- Ideal for finding leaks in exhaust after-treatment systems
- Test entire system, from intake to exhaust, in one 15 minute test
- High-pressure and large volume systems found in heavy-duty truck and turbocharged passenger vehicles


TPA 300 TPMS Programming Tool



- Activate and read TPMS sensor data, program sensors, check remote keyless entry signal and display sensor data in seconds
- Perform OBD II relearns within minutes when paired with a compatible Bosch manufactured diagnostic scan tool
- Full database of indirect, manual and auto relearn procedures
- Intuitive, full-color display with easy vehicle lookup by make, model and year
- Supports all known OE and aftermarket programmable sensors for all light vehicles
- Includes 3 years of software updates for the latest features and coverage



Are you missing YF revenue?





AC1234-9 Connected

What do I need to service R-1234yf systems?

- A new machine meeting SAE J2843 standard; Robinair's AC1234-4 or AC1234-9
- A new leak detector meeting SAE J2913 standard; Robinair's LD3, LD5 or LD7
- A syringe-type oil injector to inject oil back into the system; Robinair's 18465
- > Optional tracer gas leak detector to reduce cost searching for leak; Robinair's LD9-TG

A New Leak Detector

Your existing leak detector may not recognize R-1234yf, meaning you may not catch an expensive refrigerant leak. Invest in one that meets SAE J2913 and J2791 standards.

- LD3 leak detector automatic calibration and audible alerts
- LD5 leak detector with bar graph mode and color display
- LD7 premium leak detector with bar and pinpoint graphing modes and detects both R134a and R1234yf.



LD7 shown

New Syringe-Type Oil Injectors

1234yf systems have different fittings and couplers, requiring a new syringe-type oil injector to put oil back into the system. Current SAE standards for 1234yf service does not allow automatic oil injection on a machine.

- 18465 PAG-labeled 1234yf injector for low-voltage systems in gas and diesel vehicles
- 18470 POE-labeled 1234yf injector for electric and hybrid vehicles



18465 shown





80211TMP

Bluetooth temp probes master kit

- Read and track temperatures from multiple locations from your A/C machine
- Use up to 2 probes per compatible Robinair machine
- Enables WiFi and Bluetooth capabilities on NI and AC1234-4 machines

80211VCI

VCI master kit + database

- Enables WiFi and Bluetooth capabilities on NI and AC1234-4 machines
- Wirelessly gather and transmit vehicle year, make and model info to your compatible Robinair machine
- Includes current-year refrigerant capacity database to quickly determine correct refrigerant charge, oil type and oil capacity
- Also reads generic OBDII codes to help troubleshoot A/C system issues

What wireless accessories fit my machine?

Non-wireless A/C Machine Wireless Enabled A/C Machine

A/C Machine	VCI	Temp Probes	VCI	Temp Probes
34288NI, 34788NI, 34788NI-H, 34988NI	80211VCI	<u>80211TMP</u>	ACS-250*	80213 or 80212*
34998, AC1234-9	_	_	ACS-250**	80213 or 80212
AC1234-4	80211VCI	80211TMP	ACS-250*	80213 or 80212*

^{*}Use of ACS-250, 80212 or 80213 on NI or AC1234-4 requires machine first be WiFi/Bluetooth enabled using either 80211TMP or 80211VCI master kit

New 2024 A/C system capacity databases

- Confirm AC system charge capacities directly from your Robinair card for R-134a and R-1234yf systems, sold separately
- Includes charge amounts and component oil capacities for vehicle model years 1999 – 2023 using R-134a refrigerant and vehicle model years 2013 – 2023 using 1234yf refrigerant
- Database helps ensure the vehicle system is charged with the correct amount of oil, per factory and OEM specification

34001 R-134a database for 34998 machine

34412-G R-134a database for 34288NI, 34788NI, 34788NI-H, and 34988NI machines

R-1234vf database

34002 R-1234yf database for AC1234-9 machine

34413-E R-1234yf database for AC1234-4 machine

34414-C R-1234yf database for AC1234-6

machine

Find leaks and diagnose system issues faster

Connected accessories, leak detectors, refrigerant analyzers and tracer gas detectors

for R-134a and R-1234yf service



<u> 16995</u>

R-ID Plus refrigerant identifier/analyzer

- Analyze R-134a and R-1234yf refrigerant for purity and contamination
- Prevent contaminated refrigerant from being pulled into your machine
- Includes printer to add refrigerant purity to service report
- R-134a and R-1234yf tank adapter; R-134a and R-1234yf hoses included
- Available as 16990 R-ID without printer



EVDC100

A/C Electronic Variable Displacement Compressor Tester

- Control signal to variable compressor to accurately diagnose system problems
- Quickly diagnose and verify valve function, lowering total repair time and costs
- Includes connect adapters for both old and newer style compressors
- Heavy duty battery clips and cable provides power from vehicle battery, eliminating the need for batteries
- Made in the USA



LD7 Premium refrigerant leak detector

- Detects R-1234yf and R-134a leaks for use on most vehicles
- Sweep, bar graph and line graph modes make finding leaks faster, easier
- Features audible detection alert, UV LED lights for use with UV dye and inspection light
- Sensor life up to 10 years for reliable leak detection
- Available as LD3 and LD5 versions



LD9-TGKIT

Tracer gas leak detector service kit

- Test systems for leaks under pressure, instead of vacuum
- YF systems can hide leaks under vacuum, requiring pressure testing
- 95% Nitrogen / 5% hydrogen tracer gas mix helps find leaks faster
- Kit includes 1234yf coupler, 134a coupler, Tracer gas detector, hose and Tracer gas regulator
- Available as LD9-TG, Tracer gas detector only

^{**}Database purchase required for vehicle refrigerant capacity

R-134a Systems

Combining Simple Operation with Superior Accuracy

These machines will test, recover and recharge R-134a and R-1234yf automotive A/C system quickly and accurately.













	-		-	•	_	•
Features	<u>34288NI</u>	<u>34788NI</u>	<u>34788NI-H</u>	<u>34998</u>	AC1234-4	AC1234-9
Fully Automatic Function: Program to recover, vacuum, leak test and charge without operating panel valves.	Manual Valves	√	1	1	1	√
Automatic fluid drain/inject	Oil drain	Oil drain/inject*	Oil drain	Oil drain/inject, dye inject**	Oil drain	Oil drain
A/C System Flush: Flushes a vehicle's A/C system with refrigerant, eliminating any residual oil or other liquid. (Flushing adapters not included)	-	-	J	J	1	1
Save & print before and after service data: Allows the user to store before and after service information by vehicle and print this information to provide to a customer.	-	1	J	1	J	1
Visual & Audible Alarm: Notifies the user when service is complete, or if a problem has occurred.	-	J	1	√	1	J
Vacuum Leak Test: Monitors level after evacuation, informs of possible leak.	-	1	✓	1	1	1
Automatic Air Purge: Eliminates system-damaging air without monitoring gauges or opening valves.	✓	1	✓	1	1	✓
Automatic Refrigerant Refill: Maintains a user-selectable amount of refrigerant in an internal vessel and signals when it's time to change supply tank.	-	J	J	1	J	J
Vacuum Feature: Defaults to 15 mins, programmable up to 99 mins. "Remaining time" is displayed.	J	J	✓	√	1	√
Multilingual display	4.3" color LCD	4.3" color LCD	4.3" color LCD	10.5" hi-res touch screen	4.3" color LCD	10.5" hi-res touch screen
Refrigerant Charging:	Low only	High, low or both	High, low or both	High, low or both	High, low or both	High, low or both
Refrigerant Management System: Displays refrigerant use and monitors remaining filter life. Prompts appear when 1/3 of filter life remains.	1	1	J	1	1	1
Electric Vehicle: Capable of servicing high voltage electric compressor A/C systems.	-	_	✓	_	1	✓
Printer	30038	30038	30038	Mopria Print Service wireless printing	30038	Mopria Print Service wireless printing
Bluetooth temp probes: Dual-zone temp recording and reporting	80211TMP	80211TMP	80211TMP	80212 or 80213	80211TMP	80212 or 80213
Bluetooth VCI: Reads YMME and refrigerant capacity	80211VCI	80211VCI	80211VCI	ACS-250***	80211VCI	ACS-250***

^{*}One oil bottle. **Two oil bottles and one UV dye bottle. ***ACS-250 requires purchase of 34001 or 34002 database to read YMME and display refrigerant capacity All machines use 34724 filter and 13172 maintenance kit

Syringe-type Injectors Oil injectors for YF, EV and hybrid vehicles Use these syringe-type injectors to add oil to a fully pressurized A/C system. Fill the barrel with the amount of oil needed, connect the injector, and press the plunger. Not recommended for UV dye injection. 18480 Table 1 18470 R1234yf Oil Injectors R-134a Oil Injectors 18480 PAG labeled for 18470 POE-labeled 1234yf injector gasoline and diesel for electric and hybrid vehicles vehicles 18465 PAG-labeled 1234yf injector for 18490 POE labeled for low-voltage systems in gas and hybrid and electric diesel vehicles vehicles







TESTED AND TRUSTED SAFETY FOR LIFE

All jacks are covered by a limited lifetime warranty



ONE-HANDED BALL JOINT PRESS SETUP



CA7149

CONNECTED ADAPTER STARTER KIT

- 7 connected cups & adapters hold securely to C-frame and drive screw
- 235+ vehicle models covered, from Honda Accord to Ford F-350s
- Backwards compatible with all OTC ball joint kits and adapters



CA6630

CONNECTED ADAPTER PROFESSIONAL KIT

- 25 connected cups & adapters hold securely to C-frame, making R&I easier
- 600+ vehicle models covered, including compact cars up to HD trucks
- Fully illustrated manual with adapter callouts, diagrams and instructions by vehicle model
- Backwards compatible with all OTC ball joint kits and adapters







Navistar Tools and Diesel Engine Adapters



Heavy Duty Engine Stand and Engine Plates







1750-47366 Mack / Volvo



1750-47022 **Detroit Diesel**



6000 LB. Revolver Diesel Engine Stand

- 96 to 1 ratio worm and gear set rotates components a full 360°; handle locks in any position.
- Includes 205061 universal mounting plate for use with individual engine adapter plates.

Engine stand without universal engine adapter assembly



1750-4940 Navistar / IH



1750-4649 Navistar / IH



1750-4789 Navistar

Navistar and Detroit Diesel adapters							
Item	Description	Application	Brand	Component	Requires use of 205061 plate		
1750-47389	Detroit Diesel engine adapter plate	DD13 & DD15 engines	Detroit Diesel	Engine	No		
<u>1750-47366</u>	Mack / Volvo engine adapter plate	MP7 / D11 engines	Mack / Volvo	Engine	No		
<u>1750-4940</u>	Navistar / IH MaxxForce engine adapter plate	2010 - 2016 Navistar MaxxForce DT, MaxxForce 9, MaxxForce 10 engines	Navistar / International Harvester	Engine	Yes		
<u>1750-4649</u>	Navistar / IH MaxxForce engine adapter plate	2004 - 2009 International Harvester DT466, DT570, HT570; Navistar MaxxForce DT, MaxxForce 9, MaxxForce 10 engines	Navistar / International Harvester	Engine	Yes		
1750-4789	Navistar MaxxForce engine adapter plate	2007 - later MaxxForce 11, MaxxForce 13 engines	Navistar	Engine	Yes		
<u>1750-47022</u>	Detroit Diesel MBE 900 engine adapter plate	Detroit Diesel 2004 - 2007 MBE 900 engines	Detroit Diesel	Engine	No		

Safely lift and hold Class I, II and III vehicles - up to 3.5 tons



LDJA2 2-ton aluminum racing jack

- Lift compact sedans to small crossovers
- Light, sturdy aircraft aluminum with carry handles is ideal for service trucks and portability

SA02 2-ton aluminum jack stands

- Pin-style jack stand for fast, secure vehicle holding
- Aircraft aluminum construction for rust-free performance

LDJA2-SET

• Includes LDJA2 2-ton aluminum jack and SA02 2-ton aluminum stands



LDJ3-A 3-ton service jack

• Ideal for utility vans, full size sedans, pickups, and SUVs

LDJ35 3.5-ton steel service jack

- Safely handles large SUVs and crossovers to 3/4-ton pick-ups
- Rolled edges add strength to resist twisting for larger loads



<u>\$03</u> 3-ton steel jack stands \$04 4-ton steel jack stands

- Ratcheting design cannot be released under load
- Formed and welded steel base with baked enamel finish for strength, corrosion resistance
- S03 and S04 sold as a pair







Service Jacks

	LDJA2	LDJ3-A	<u>LDJ35</u>
Capacity	2-ton	3-ton	3.5-ton
Lifting range	3-1/4" (saddle removed) - 18-5/8"	2.95" - 20"	5.2" to 21.9"
Padded handle length	47.6"	46.25"	50" spring-loaded padded lower handle
Footprint	11.875" x 25.125"	13.5" x 28.5"	14.5" x 28.5"
Reach	72.75"	78.5"	78.5"
Saddle	4-1/2" dia., round	4" dia., steel crown	6" dia., flat steel, rubberized, pinned to lifting arm
Casters	4; 2.5" front fixed (2), 1.75" rear swivel (2)	4; 2.4" front fixed (2), 2.4" rear swivel (2)	4; 3.15" front fixed (2), 2.5" rear swivel (2)
Frame height	6"	6.1"	6.25"







Jack Stands

	SA02 (sold as a pair)	<u>S03</u> (sold as a pair)	S04 (sold as a pair)
Capacity	2-ton	3-ton	4-ton
Max height	15.44"	17-11/16"	23-13/16"
Min height	9-1/2"	12"	15-1/2"
Footprint	7" round base	8-1/4" x 7-1/2" square base; welded foot pads	Square base; welded foot pads
Adjustment	Pin lock; 6 slots	Ratcheting; 11 teeth	Ratcheting; 11 teeth
Saddle	Flat-top style, 2.17" x 2"	V-notch style, 1" x 3.5"	V-notch style, 1.3" x 4.3"

Covering the big classes for lifting it all



HDJ5 5-ton hydraulic service jack

- Designed to safely lift step vans and bucket trucks
- 3-position handle lays flat, 45° or 90° for storage and use

HDJ5P 5-ton hydraulic service jack with air-assist

• Same as HDJ5, with air/hydraulic assist to reduce effort to raise, lower vehicles



HDJ10 10-ton hydraulic service jack

- Ideal for bucket trucks and school buses
- Rugged steel frame and extra-large wheels for durability and strength

HDJ10P 10-ton hydraulic service jack with air-assist

Same as HDJ10, with air/hydraulic assist to reduce effort to raise, lower vehicles



HDJ20 20-ton hydraulic service jack

- 3-position spring-loaded handle can lay flat, 45° or 90°
- Foot and hand pump options to raise load quickly

HDJ20P 20-ton hydraulic service jack with air-assist

Same as HDJ20, with air/hydraulic assist to reduce effort to raise, lower vehicles





5, 10, 20-ton heavy-duty jacks	<u>HDJ5</u>	HDJ5P	<u>HDJ10</u>	HDJ10P	HDJ20	HDJ20P
Capacity	5-ton	5-ton air-assist	10-ton	10-ton air-assist	20-ton	20-ton
Lifting range	6" to 22"	5-7/8" to 22"	6.3" to 22"	6-3/8" to 22"	7-1/2" to 23.8"	7-1/2" to 23.8"
Air pressure	_	80-120 PSI	_	80-120 PSI	_	80 - 120 PSI
Handle length	43" 3-position with lock and release controls	45.4" 3-position with lock and release controls	43-1/4" 3-position with lock and release controls	45.4" 3-position with lock and release controls	47-1/2", 3-position spring-assisted locking	47-1/2", 3-position spring-assisted locking
Footprint	15" x 56"	14.2" x 55.5"	18" x 60"	18.9" x 60.8"	18-1/8" x 61-3/8"	18-1/8" x 61-3/8"
Reach	47"	87"	51"	90"	110.4"	110.4"
Saddle	5-1/8" dia., round	5.1" dia., round	6" dia., round	5-3/4" dia., round	6-1/2" dia., steel crown	6-1/2" dia., steel crown
Casters	4; 4.4" fixed front (2), 2.8" mid-body swivel (2)	4; 4.4" fixed front (2), 2.8" mid-body swivel (2)	4; 5.6" fixed front (2), 3.6" mid-body swivel (2)	4; 5.6" fixed front (2), 3.6" mid-body swivel (2)	6; 4 front fixed; 2 mid-body swivel	6; 4 front fixed, 2 mid-body swivel
Frame height	7.9"	7.5"	9.8"	9.8"	10.2"	10.2"



S06 6-ton steel jack stands

- Ratcheting design cannot be released under load
- Formed and welded steel base with baked enamel finish for strength, corrosion resistance



S012 12-ton jack stands

- Pin-style stand increases contact points for increased holding strength
- Form-fit saddle and wide base ensures stability of heavy loads



S020 20-ton steel jack stand

- Large 15-1/2" square base safely holds up to 40,000 lbs
- Dual pin-style stand with four adjustment positions



S022 22-ton steel jack stands

- 11" flat square base prevents sinking into concrete or other surfaces
- Large flat base rated to safely hold up to 44,000 lbs
- Pin Style Stand with 3 adjustment positions

Heavy-duty stands	S06 (sold as a pair)	S012 (sold as a pair)	<u>S020</u> (single)	S022 (sold as a pair)
Capacity	6-ton	12-ton	20-ton	22-ton
Max height	23-11/16"	27-1/2"	24"	19-7/8"
Min height	15-5/8"	17-1/2"	15-1/4"	13-7/8"
Footprint	11-9/16" x 10-3/8" square base; welded foot pads	12-1/8" x 10-7/8" plus-sign style flat base	15-1/2" square base	11" square base, flat for maximum ground contact
Adjustment	Ratcheting; 11 teeth	Single pin-style	Dual-pin; 4 slots	Pin-style; 3 slots in 3" increments
Saddle	V-notch style, 1.2" x 4.2"	Flat-top horseshoe style	6" dia., round steel	3" x 3-3/4" V-notch

Under-axle service jack	<u>UA22</u>	<u>UA27</u>
Capacity	22-ton	27.5-ton
Air pressure	90 - 145 PSI	90 - 175 PSI
Max height	20-2/3" with longest saddle	21-3/8" using longest saddle
Min height	8.27"	8-1/4"
Handle length	47.24" T handle with lowering lever and air- chuck hook	48-3/4" T handle with lowering lever and air- chuck hook
Footprint	22.63" x 11.73"	22" x 12"
Reach	69.87"	69.87"
Saddle	3" dia., round with center notch, includes 3 lengths	3" dia., round with center notch. Includes 2 saddle adapters
Frame height	8.27"	8.27"
Wheels	2 fixed; 7.88" rubberized steel	2 fixed; 7.88" rubberized steel



New OTC Bottle Jacks

All OTC bottle jacks meet or exceed the newest ASME PASE-2019 safety standards for portable automotive service equipment. This includes a built-in safety valve to prevent overloading, and a stable base to prevent tipping if loaded off-center.

Air assisted jacks can be operated manually or with shop air. Minimum air pressure required is 100 PSI to move ram and lift objects.













Bottle Jacks	<u>BT12</u>	<u>BT30</u>	<u>BT12P</u>	<u>BT20P</u>	<u>BT30P</u>
Capacity	12-ton	30-ton air-assist	12-ton	20-ton air-assist	30-ton air-assist
Lifting range	9-3/8" to 18-5/8"	11" to 17-5/8"	9-1/2" to 18-3/8"	9-7/16" to 17-11/16"	11" to 17-5/8"
Stroke	6"	6-5/8"	6-1/8"	5-7/8"	6-5/8"
Air pressure	-	-	100-120 PSI	100-120 PSI	100 - 120 PSI
Screw extension length	3-1/4"	-	2-3/4"	2-5/16"	2-3/4"
Pumps to extend piston one inch	21	41	21	28	41
Saddle	1-3/4"	2-1/2"	1-3/4"	2-1/8"	2-1/2"
Carry handle	Yes	Yes	Yes	Yes	Yes
Weight	18.9 lbs	43.2 lbs	16.1 lbs	19.5 lbs	43.2 lbs
Warranty	Limited lifetime	Limited lifetime	Limited lifetime	Limited lifetime	Limited lifetime



Angled Wire Stripping Tool

- Unique design puts stripping dies on the angled tip
- Patented design makes for easier use in hard to reach places
- Works on 12 to 20 AWG wire

CrimPro™ 4-in-1 Angled Wire Tool

5950A

- The angled feature allows access to close quarters and facilitates superior crimps
- Compact 7-inch design used 4 ways
- Gripping nose to pull, twist, bend, and shape
- Crimper crimps 12-20 AWG insulated and noninsulated wire
- Stripper strips 12-20 AWG wire.
- Cutter ability to make cuts below pivot.



CrimPro™ 4-in-1 Wire Tool

- Compact 7-inch design used 4 ways
- Gripping nose to pull, twist, bend, and shape
- Crimper crimps 12-20 AWG insulated and non-insulated wire
- Stripper strips 12-20 AWG wire
- · Cutter ability to make cuts below pivot



4247-FR

Suspension Bushing Kit with Pump

This heavy-duty suspension bushing tool replaces worn-out, rusted, and frozen double-wrap spring bushings faster and easier without heat or damage by providing a 25-ton capacity.

- The tool can be assembled on the spring and bushing without removing the assembly from the vehicle, dramatically reducing service time and not requiring the use of a shop press.
- Patent-pending design allows for unassisted assembly of the tool onto the spring, eliminating
 the need to hold any weight of the tool during operation. The press plates and adapters are
 easily installed which perfectly align the bushing to reduce the chance of misalignment and
 bushing damage during removal or installation.
- Kit includes Air/Hydraulic pump, 25-ton hydraulic cylinder, hose w/couplers, complete puller leg/plates, and adapter set.
- The tool and adapters included in this kit allow for service of the following applications:
- Hendrickson rear suspensions including: Primaax EX, Comfort Air and FCCC V-Ride (TM) Pivot and D-Pin suspension bushings.
- Freightliner rear suspensions including: Double and single-wrapped FAS II Airliner rear suspension bushings.



<u>4254-FR</u>

Suspension Bushing Adapter Kit

This heavy-duty suspension bushing tool replaces worn-out, rusted, and frozen double-wrap spring bushings faster and easier without heat or damage by providing a 25-ton capacity, when used with OTC service sets 4247, 4275, 4261, or 4263.

- The tool can be assembled on the spring and bushing without removing the assembly from the vehicle, dramatically reducing service time and not requiring the use of a shop press.
- Patent-pending design allows for unassisted assembly of the tool onto the spring, eliminating the need to hold any weight of the tool during operation. The press plates and adapters are easily installed which perfectly align the bushing to reduce the chance of misalignment and bushing damage during removal or installation.

The adapters included in this kit allow for service of the following applications:

- Hendrickson rear suspensions including: Primaax EX, Comfort Air and FCCC V-Ride (TM) Pivot and D-Pin suspension bushings.
- Freightliner rear suspensions including: Double and single-wrapped FAS II Airliner rear suspension bushings.
- For use with OTC service sets 4247, 4275, 4261, or 4263



CA6636-EXT

Connected Adapter Ball Joint Extension

Allows the CA6636 Connected Adapter C-Frame to be oriented in either direction by providing extra clearance for ball joint studs on the drive screw side.



<u>6740</u>

Crankshaft Rear Seal Remover

Save time removing crankshaft rear seals, preventing damage to the block and crank. Prying the crankshaft seal out can damage expensive engine components. This seal remover is a special puller with three jaws designed to grab the inner lip of the seal. The forcing screw attached to the center plate is used to react against the crankshaft end to pull the seal out. This eliminates damage to the block and crank that prying the seal can cause.

Applications include GM 6.6L Duramax diesel engines found in:

- 2001-Later GMT800 platform vehicles, including Chevrolet Silverado and GMC Sierra 2500HD, 3500
- 2001-Later GMT900 platform vehicles, including GMC Sierra HD and Chevrolet Silverado HD 2006-2016

Similar to OE tool #J-44641.



<u>6777</u>

GM Duramax Injector Puller

Assists in removing injectors from the cylinder head without damaging the injector body. Similar to OE tool #EN-49774.

Applications include 2011-later 6.6L Duramax Diesel and Isuzu engines



Cone Washer Removal Adapter

The OTC 5098 is an air hammer attachment designed to break loose cone washers on floating axle dual rear wheel setups. The patented, hollow-center tool slides over the stud, making direct contact with the cone washer to vibrate it free.



1797

Heavy-duty clutch adapter

A special transmission jack adapter to handle heavy-duty clutch assemblies during service. Universal mounting slots in the base for a universal fit on most high and low-lift transmission jacks. The built-in splined adapter mount rotates easily to help align to the clutch spline and align the clutch to the flywheel.

- Includes safety strap to hold the clutch securely when maneuvering or working.
- For use with 10 and 14-splined adapters, not included. Fits OTC and other high-lift and low-lift transmission jacks



60000!

Splined Shaft Adapter for 5018A Clutch Handler

Optional splined shaft adapter for Eaton Fuller UltraShift Plus Transmission, 14 Spline, 2" OD, 1.18" Pilot. For use with the OTC 5018A Clutch Handler. Includes part number 600007 clutch handler shaft adapter allowing splined shafts designed for the 5015A to be used on the 5018A.

MUSCLETOOLS



Shop-ready Solutions

EV Chargers from Bosch

Reduced installation cost

- No need to cut or modify during installation
- •Install with local certified electrician
- No specialized training required
- •No payment system required
- No additional networking infrastructure costs during installation

Low total cost of ownership

- No app required
- No maintenance
- No monthly maintenance and/ or Wi-fi fees
- Simple plug and play
- •UL/cUL/ETL/cETL Safety Listed on full product not just components

Prepare your shop to work on EVs

Prepare your shop to work on EVs with our Bosch EV Service Checklist.





Visit boschevsolutions.com/ ev-checklist



EV3000 30kW DC Fast Charger

- Indoor & Outdoor Use
- Charge up to 4 times faster than Level 2 AC charging stations
- Requires a dedicated circuit
- 17 ft Cable
- 3-year warranty

EV810 Level 2 Charger

- Indoor & Outdoor Use
- Fixed Mount
- 18 Ft Cable
- 3-year warranty

EV410 Level 2 Charger

- Indoor & Outdoor Use
- 25 ft Charge Cable
- Made in USA



Bosch Mobility Aftermarket offers a comprehensive portfolio of unmatched solutions for every job. From diverse diagnostic solutions and OE-quality auto parts, to industry-leading software and unmatched vehicle coverage, to innovative charging, repair and maintenance tools. Bosch has solutions for every shop.

Committed to quality because your reputation depends on it.

Bosch Customer Service 800 321-4889 (Ext. 4, Option 2)

OTC and Robinair Customer Service 800 533-6127 (Option 1)

24060611_Muscle Tools_Q3 2024 edition, Printed in U.S.A.



- Movable

- 4-year warranty

EV850 Level 2 Charger

- Indoor & Outdoor Use
- Single Bollard in Stainless enclosure
- 23 ft Cable
- 3-year warranty

EV860 Level 2 Charger

Same as EV850 with two Chargers